

Manual Call Points



Intelligent/Addressable Devices

General

Notifier addressable Manual Call Points (MCP's) are designed to be used as a component of a fire control system.

These MCP's are designed for use on the two wire communication circuit providing both signalling of an alarm to the fire indicator panel and local LED indication of activation.

FSM500K

This MCP is designed for internal use and an optional mounting box is available for ease of mounting and termination of cabling.

The glass filament is laminated to prevent any physical damage to the person operating the device.

Features

- CSIRO Approved
- Two wire connection for easy installation
- Suitable for flush mounting or surface mounting
- Simple rotary decade setting
- Integral LED controlled from panel

WCP-5A-R

This MCP is designed for external use and comes complete with a mounting box for ease of installation and termination of cabling.

Features

- CSIRO Approved
- Two wire connection for easy installation
- Sealed to IP67.
- Anti-tamper facility.
- Enhanced aesthetics and compact design.
- Unique 'Plug & Play' installation concept.
- Total 'Flex-Ability' in the choice of operating element.
- Simple rotary decade setting
- Integral LED controlled from panel



FSM500K



WCP-5A-RSG

Approvals

FSM500K

CSIRO ActivFire listed to EN 54-11
(Type A):2001 afp-2259

WCP-5A-RSG

CSIRO ActivFire listed to EN 54-11
(Type A):2001 afp-2261

Specification

FSM500K

Operating Voltage:	15 - 32VDC
Current Rating:	
Standby:	200µA
Alarm:	5mA
LED Rating:	Max. 30mA
Temperature Range:	0°C to 49°C
Humidity Range:	10% to 93% non-condensing
IP Rating:	IP24
EOL Value:	47K ohms.

WCP-5A-RSG

Maximum Voltage:	30VDC
Switch Rating:	2A
LED Rating:	Max. 30mA
Temperature Range:	-30°C to 70°C
Humidity Range:	0% to 95% non-condensing
IP Rating:	IP67
EOL Value:	47K ohms.

Ordering Information

FG-05-019	FSM500-K "Fire" Intelligent Flashscan Manual Call Point - Red
FG-05-020	WCP-5A-RSG "Fire" Intelligent Weatherproof Manual Call Point - Red
FG-18-019	Spare Glass for all MCP's
FG-18-020	Spare flap for FSM500-K MCP's
FG-18-021	Spare flap for all KAC MCP's
FG-18-022	Re-settable element for all KAC MCP's
FG-18-023	Spare test key for all MCP's

© 2009 by Honeywell International Inc. All rights reserved.
Unauthorised use of this document is strictly prohibited.

This document is not intended for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor
www.notifier.com.au