

FRM-1

Relay Module



Intelligent/Addressable Devices

General

The FRM-1 Addressable Relay Module provides the system with a dry-contact output for activating a variety of auxiliary devices, such as fans, dampers, control equipment, etc. Addressability allows the dry contact to be activated, either manually or through panel programming, on a select basis.



Features

- Built-in type identification automatically identifies these devices to the control panel.
- Internal circuitry and relay powered directly by two-wire SLC loop.
- Integral LED “blinks” green each time a communication is received from the control panel and turns on in steady red when activated.
- LED blink may be deselected globally (affects all devices).
- High noise immunity (EMF/RFI).
- Wide viewing angle of LED.
- Direct-dial entry of address 01– 159 for FlashScan loops, 01 – 99 for CLIP mode loops.
- Compatible with FlashScan® and CLIP protocol systems

Operation

Each FRM-1 uses one of 159 possible module addresses on a SLC loop (99 on CLIP loops). It responds to regular polls from the control panel and reports its type and status, including the open/normal/short status of its Notification Appliance Circuit (NAC). The LED blinks with each poll received. On command, it activates its internal relay.

Applications

The FRM-1 may be programmed to operate dry contacts for applications such as door holders and Air Handling Unit shutdown.

Specifications

Normal operating voltage:	15 to 32 VDC.
Maximum current draw:	6.5 mA (LED on).
Average operating current:	230 μ A direct poll; 255 μ A group poll.
EOL Value:	Not used.
Temperature range:	0°C to 49°C.
Humidity range:	10% to 93% non-condensing.
Current Ratings:	3.0 A @ 30 VDC resistive, non-coded. 2.0 A @ 30 VDC resistive, coded. 0.9 A @ 110 VDC resistive, non-coded. 0.9 A @ 125 VDC , resistive, non-coded. 0.5 A @ 30 VDC inductive (L/R = 5 ms), coded. 1.0 A @ 30 VDC inductive (L/R = 2 ms), coded. 0.3 A @ 125 VDC inductive, (PF=0.35), non-coded. 1.5A @ 25 VDC , inductive, (PF=0.35), non-coded. 0.7 A @ 70.7 VDC inductive, (PF=0.35), non-coded. 2.0A @ 25 VDC , inductive, (PF=0.35), non-coded.

NOTE: Maximum (Speakers): 70.7 V RMS, 50 W

© 2009 by Honeywell International Inc. All rights reserved.
Unauthorised use of this document is strictly prohibited.

This document is not intended for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor
www.notifier.com.au