

# SOU Series Wall Mount Sounders



## Ancillary Devices

### General

Notifier's SOU Series wall mount sounders have a distinctive low profile shape which is acoustically very efficient, producing high sound output at low current levels.

The wall mount sounders have a wide angle uniform sound distribution providing good audibility in all directions.

Rugged construction with solid state electronics also provides high reliability and stable performance.

### Features

- Four selectable tones including temporal.
- High sound output (up to 103dB).
- Low current consumption.
- Volume control.
- Low profile, surface and waterproof mounting versions.



**SOU-LPR-4**



**SOU-SSR-4**



**SOU-SSW-4**

## Specifications

Operating Voltage:	15 to 33VDC
Current Consumption:	11mA @ 24VDC (High Setting)
Sound Output:	103dB(A) high 100db(A) medium 97db(A) low @24VDC
Operating Temperature:	-30oC to 70oC
Relative Humidity:	Up to 95% @ 55oC (with srface base)
Ingress Protection:	IP44 (with low profile base) IP66 (Waterproof base)
Volume Settings:	High, medium, low

## Ordering Information

11187	SOU-SSR-4 4 Tone, Red, Waterproof Sounder
11198	SOU-LPR-4 4 Tone, Red, Low Profile Sounder
11201	SOU-SSW-4 4 Tone, White, Waterproof Sounder

---

© 2009 by Honeywell International Inc. All rights reserved.  
Unauthorised use of this document is strictly prohibited.

---

This document is not intended for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor  
[www.notifier.com.au](http://www.notifier.com.au)

---