

Manual Call Points

Conventional Devices

General

Notifier conventional Manual Call Points (MCP's) are designed to be used as a component of a fire control system.

These MCP's are come in three variants; indoor flush or surface mount and a weatherproof version for use outdoors or in areas where moisture or dust are present.

Features

- CSIRO Approved.
- Sealed to IP24, weatherproof version to IP67.
- Indoor version suitable for flush mounting or surface mounting.
- Anti-tamper facility.
- Enhanced aesthetics and compact design.
- Unique 'Plug & Play' installation concept.
- Total 'Flex-Ability' in the choice of operating element.

Approvals

Indoor

CSIRO ActivFire listed to EN 54-11
(Type A):2001 afp-2258

Weatherproof

CSIRO ActivFire listed to EN 54-11
(Type A):2001 afp-2260



Flush Mount



Surface Mount



Weatherproof

Specification

Maximum Voltage:	30VDC
Switch Rating:	2A
LED Rating:	Max. 30mA
Temperature Range:	-10°C to 55°C
Humidity Range:	0% to 95% non-condensing
IP Rating:	IP67
EOL Value:	47K ohms.

Ordering Information

FG-18-009	MCP-3A-RFG "House Flame" Conventional Manual Call Point - Red -Flush mount
FG-05-020	MCP-3A-RSG "House Flame" Conventional Manual Call Point - Red -Surface mount
FG-05-008	WCP-3A-RSG "House Flame" Weatherproof Manual Call Point - Red -Surface mount
FG-18-019	Spare Glass for all MCP's
FG-18-021	Spare flap for all KAC MCP's
FG-18-022	Re-settable element for all KAC MCP's
FG-18-023	Spare test key for all MCP's

© 2009 by Honeywell International Inc. All rights reserved.
Unauthorised use of this document is strictly prohibited.

This document is not intended for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor
www.notifier.com.au