

Ceiling Speakers

General

These speaker units have been engineered to meet the demanding requirements of the relevant Australian Standards for background music, paging and EWIS applications.

Features

- Patented transformer safety cover.
- 4 way wire protect terminal.
- Professional grade grain oriented steel transformer cores
- Speaker drivers have been chosen for optimum frequency response and efficiency.



**100mm & 200mm
Flush Mount**



**100mm & 200mm
Grill**



**100mm
One Shot**



**100mm & 200mm
Surface Mount**

Specifications

Voltage:	100V
Impedance:	8 ohm
Output Power:	0.33W, 0.66W, 1.25W, 2.5W, 5W
Sound Pressure Level:	92dB (1W @ 1m)
Connection:	4 way terminal block plus 22µf bipolar capacitor

Ordering Information

Part Number	Description
1390	SP/100 100mm Flush mount speaker
11115	SP/100/LP 100mm Flush mount low profile speaker
11834	SP/100/H 100mm High output flush mount speaker
1917	GRILL/100 100mm Ceiling grill
10288	SP/100/OS 100mm Flush mount quick fit speaker & grill
1546	SP/100/SM 100mm Surface mount speaker c/w grill
1391	SP/200 200mm Flush mount speaker
1524	GRILL/200 200mm Ceiling grill
11902	SP/200/OS 200mm Flush mount quick fit speaker & grill
11756	SP/200/SM 200mm Surface mount speaker c/w grill

© 2009 by Honeywell International Inc. All rights reserved.
Unauthorised use of this document is strictly prohibited.

This document is not intended for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor
www.notifier.com.au