

Manual Call Points



Evacuation

General

Notifier evacuation Manual Call Points (MCP's) are designed to be used as a component of an Emergency Warning & Intercommunication System (EWIS) or Building Occupant Warning System (BOWS).

These MCP's come in two variants; indoor surface mount and a weatherproof version for use outdoors or in areas where moisture or dust are present.

Features

- Sealed to IP24, weatherproof version to IP67.
- Anti-tamper facility.
- Enhanced aesthetics and compact design.
- Unique 'Plug & Play' installation concept.
- Total 'Flex-Ability' in the choice of operating element.



Surface Mount



Weatherproof

Specification

Maximum Voltage:	30VDC
Switch Rating:	2A
LED Rating:	Max. 30mA
Temperature Range:	-10°C to 55°C
Humidity Range:	0% to 95% non-condensing
IP Rating:	IP67
EOL Value:	47K ohms.

Ordering Information

FG-05-011	MCP-3A-WSG "Emergency Alarm" Manual Call Point - White -Surface mount
FG-05-002	WCP-3A-WSG "Emergency Alarm" Weatherproof Manual Call Point - White -Surface mount
FG-18-019	Spare Glass for all MCP's
FG-18-021	Spare flap for all KAC MCP's
FG-18-022	Re-settable element for all KAC MCP's
FG-18-023	Spare test key for all MCP's

© 2009 by Honeywell International Inc. All rights reserved.
Unauthorised use of this document is strictly prohibited.

This document is not intended for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor
www.notifier.com.au
