

Manual Call Points Intrinsically Safe



Industrial Application Devices


General

Notifier supply a range of intrinsically safe Manual Call Points (MCP's) in colours suitable for most applications.

Features

- ATEX approved.
- Sealed to IP24, weatherproof versions to IP67.
- Indoor versions suitable for flush mounting or surface mounting.
- Anti-tamper facility.
- Enhanced aesthetics and compact design.
- Unique 'Plug & Play' installation concept.
- Total 'Flex-Ability' in the choice of operating element.

Approvals

-  II 1 G EEx ia II CT4
Sira 04ATEX2350X
- EN 60079-0:2006
EN 60079:26:2007
EN 60079:11:2007
EN 61241-0:2005
IEC 61241-11:2005
- **LPCB 166b**



Surface Mount



Weatherproof

Specification

Maximum Voltage:	30VDC
Switch Rating:	2A
LED Rating:	Max. 30mA (Addressable version only)
Temperature Range:	-30°C to 70°C
Humidity Range:	0% to 95% non-condensing
IP Rating:	Indoor IP24D Weatherproof IP67
EOL Value:	47K ohms.

Ordering Information

FG-05-020	WCP-5A-RSG-IS "House Flame" Weatherproof Addressable Manual Call Point - Red - Surface mount - Intrinsically Safe
FG-18-030	MCP-3A-RSG-IS "House Flame" Manual Call Point - Red - Surface mount - Intrinsically Safe
FG-18-031	WCP-3A-RSG-IS "House Flame" Weatherproof Manual Call Point - Red - Surface mount - Intrinsically Safe
FG-18-032	MCP-3A-YSG-IS "Extinguishant Release" Manual Call Point - Yellow - Surface mount - Intrinsically Safe (inc hinged cover)
FG-18-033	WCP-3A-YSG-IS "Extinguishant Release" Weatherproof Manual Call Point - Yellow - Surface mount - Intrinsically Safe (inc hinged cover)
FG-18-034	MCP-3A-BSG-IS Plain Manual Call Point - Blue - Surface mount - Intrinsically Safe
FG-18-035	WCP-3A-BSG-IS Plain Weatherproof Manual Call Point - Blue - Surface mount - Intrinsically Safe
FG-18-036	MCP-3A-GSG-IS "Emergency Door Release" Manual Call Point - Green - Surface mount - Intrinsically Safe
FG-18-037	WCP-3A-GSG-IS "Emergency Door Release" Weatherproof Manual Call Point - Green - Surface mount - Intrinsically Safe
FG-18-019	Spare Glass for all MCP's
FG-18-021	Spare flap for all KAC MCP's
FG-18-022	Re-settable element for all KAC MCP's
FG-18-023	Spare test key for all MCP's

© 2009 by Honeywell International Inc. All rights reserved.
Unauthorised use of this document is strictly prohibited.

This document is not intended for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

For more information contact your nearest Notifier Sales Office or Distributor
www.notifier.com.au